


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H02K 1/18</b>	<b>A1</b>	(11) International Publication Number: <b>WO 98/20596</b> (43) International Publication Date: <b>14 May 1998 (14.05.98)</b>
<p>(21) International Application Number: <b>PCT/SE97/01842</b></p> <p>(22) International Filing Date: <b>4 November 1997 (04.11.97)</b></p> <p>(30) Priority Data: <b>9604028-2</b> <b>4 November 1996 (04.11.96)</b> <b>SE</b></p> <p>(71) Applicant (for all designated States except US): <b>ASEA BROWN BOVERI AB [SE/SE]; S-721 83 Västerås (SE).</b></p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): <b>ROTHMAN, Bengt [SE/SE]; Profilgatan 16, S-723 36 Västerås (SE).</b></p> <p>(74) Agent: <b>ASKERBERG, Fredrik; L.A. Groth &amp; Co. KB, P.O. Box 6107, S-102 32 Stockholm (SE).</b></p>	<p>(81) Designated States: <b>AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, FI (Utility model), GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</b></p> <p><b>Published</b> <i>With international search report.</i> <i>With amended claims.</i></p>	

(54) Title: LAMINATED MAGNETIC CORE FOR ELECTRIC MACHINES

## (57) Abstract

The present invention relates to a laminated magnetic core for rotating electric machines. The laminated magnetic core comprises a number of stack members (40), each consisting of a number of sheets of metal joined together. Each stack member (40) is provided with two identical grooves (42) arranged to cooperate with wedge members (46) designed to join the stack members (40). The cross-sectional area of the groove (42) is larger than the cross-sectional area of the wedge member (46) and the wedge member (46) has two protrusions arranged symmetrically in relation to the longitudinal axis of the wedge member. The groove (42) has at least one part shaped to fit said protrusion. The stack members (40) in the laminated magnetic core are stacked on and partially overlapping each other to form different layers of stack members (40). The grooves (42) in the stack members (40) in the various layers are arranged substantially opposite each other with the wedge members (46) arranged in the grooves (42) and a protrusion abutting the complementary shape of the groove (42) in such a manner that the stack members (40) in one layer are secured counter-clockwise in tangential direction and that the stack members in at least one of the adjacent layers are secured clockwise in tangential direction. The laminated magnetic core also includes locking members arranged at least at the transition between layers secured clockwise and layers secured counter-clockwise in order to prevent tangential movement between the different layers.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Laminated magnetic core for electric machines.

TECHNICAL FIELD:

The present invention relates to a laminated magnetic core for rotating electric machines and a rotating electric machine comprising such laminated magnetic  
5 core.

The machine is in the first place intended as a generator in a power station for generating electric power.

10

The invention is applicable to rotating electric machines such as synchronous machines and normal asynchronous machines. The invention is also applicable to other electric machines such as dual-fed machines and applications in asynchronous static current converter cascades, outerpole machines and  
15 synchronous flow machines provided their windings are manufactured with insulating electric conductors, and preferably for high voltages. High voltages shall be understood here to mean electric voltages in excess of 10 kV.

BACKGROUND ART:

20 Similar machines have conventionally been designed for voltages in the range 15-30 kV, and 30 kV has normally been considered to be an upper limit. This usually means that a generator must be connected to the power network via a transformer which steps up the voltage to the level of the power network - in the range of approximately 130-400 kV.

25

A machine which can operate at higher power levels and which can be directly connected to a power network is known from PCT/SE97/00874.

The laminations in laminated stator cores (laminated magnetic cores) for large  
30 electric machines are normally laid one by one with overlap in such a way that grooves in the laminations match facing surfaces in the dovetail-shaped wedge of the stator frame. (See Figure 2.) To enable the lamination to assume its position it is bent sufficiently for the dovetail-shaped groove part to pass the surface of the dovetail-shaped wedge. This method of manufacture is relatively complicated,  
35 time-consuming and thus expensive.

## SUMMARY OF THE INVENTION:

The object of the present invention is to solve the problems mentioned above. This is achieved with a laminated magnetic core for rotating electric machines as defined in claim 1, and a rotating electric machine comprising a laminated magnetic core of the type described above as defined in claim 10. The laminated magnetic core according to the present invention comprises a number of stack members, each consisting of a number of sheets of metal joined together. Each stack member is provided with two identical grooves arranged to cooperate with wedge members designed to join the stack members together. Each wedge member has two protrusions arranged symmetrically in relation to the longitudinal axis of the wedge member. Each groove in the stack member has at least one part shaped to fit said protrusion. The stack members in the laminated magnetic core are stacked on and partially overlapping each other to form different layers of stack members, the grooves in the stack members in the various layers being arranged substantially opposite each other. The wedge members are arranged in the grooves with a protrusion abutting the complementary shape of the groove in such a manner that the stack members in one layer are secured counter-clockwise in tangential direction and that the stack members in at least one of the adjacent layers are secured clockwise in tangential direction. The laminated magnetic core also includes locking members arranged at least at the transition between layers secured clockwise and layers secured counter-clockwise in order to prevent tangential movement between the different layers.

The above-mentioned laminated magnetic core according to the present invention is easy and quick to manufacture. It is thus also relatively inexpensive to manufacture.

## BRIEF DESCRIPTION OF THE DRAWINGS:

The invention will be explained in more detail in the following description of preferred embodiments thereof, with reference to the accompanying drawings in which

Figure 1 shows a cross-sectional view of a high-voltage cable;

- Figure 2 shows a side view of a sheet of metal and a part of a wedge member according to the state of the art, which is included in a laminated magnetic core according to the state of the art;
- 5 Figure 3 shows a basic diagram explaining how the various sheets of metal are joined in relation to each other in a laminated magnetic core according to the state of the art;
- 10 Figure 4 shows a side view of a stack member and a part of wedge members included in a laminated magnetic core according to a first embodiment of the present invention;
- 15 Figure 5 shows a side view on an enlarged scale of how stack members in different layers are joined together by means of the wedge member in a laminated magnetic core according to the first embodiment of the present invention;
- 20 Figure 6 shows a side view of a laminated magnetic core according to the present invention; and
- 25 Figure 7 shows a side view on an enlarged scale of how stack members in different layers are joined together by means of the wedge member in a laminated magnetic core according to a second embodiment of the present invention.
- Figure 8 shows a side view of a stack member according to an alternative embodiment of the invention.

#### DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION:

- 30 Figure 1 shows a cross-sectional view of a high-voltage cable 10 which is traditionally used for conducting electric power. The high-voltage cable 10 may be a standard PEX-cable 145 kV but without sheath or screen. The high-voltage cable 10 comprises an electric conductor that may consist of one or more strand parts 12 made of copper (Cu), for instance, and having circular cross section.
- 35 These strand parts 12 are arranged in the middle of the high-voltage cable 10. Around the strand parts 12 is a first semiconducting layer 14. Around the first

semiconducting layer 14 is a first insulating layer 16, e.g. PEX insulation. Around the first insulating layer 16 is a second semiconducting layer 18.

Figure 2 shows a side view of a sheet of metal 20 and a part of a wedge member 22 according to the state of the art included in a laminated magnetic core according to the state of the art. Each sheet of metal 20 is normally 0.35-0.50 mm thick and is provided with two grooves 24 arranged along the outer long side of the sheet 20. As can be seen in Figure 2, the inner and outer long sides of the sheet 20 have different radii or curvature so that when the sheets 20 are fitted together to form a laminated magnetic core it will be cylindrical. The sheets 20 are also provided with a number of slots 26 arranged along the inner long side. These slots 26 are intended for stator windings in the assembled laminated magnetic core. The wedge members 22 (only a part of one wedge member 22 is shown) are arranged on the stator frame (not shown) and have a dovetail-shaped cross section at the end shown. The grooves 24 arranged along the outer long side of the metal sheet 20 have an inclined flank 28 and a straight, perpendicular flank 30. As can be seen in Figure 2 both the inclined flanks 28 of the grooves 24 in each metal sheet 20 face each other. When the metal sheets 20 are to be assembled to form a laminated magnetic core, they are applied one by one and partially overlapping each other (see Figure 3). The wedge members 22 are permanently arranged on the stator frame and have a length in a direction perpendicular to the drawing that is equal to the length of the laminated magnetic core. To enable a metal sheet 20 to assume its proper position the metal sheet 20 must be bent so far that the inclined flanks 28 of the grooves 24 can pass the dovetail-shaped surfaces of the member 22. This means that the inclined flanges 28 of the metal sheet 20 match facing surfaces of the dovetail-shaped wedge member 22.

Figure 3 shows a basic diagram explaining how the different metal sheets are joined in relation to each other in a laminated magnetic core according to the state of the art. The sheets and wedges used may be as shown in Figure 2, for instance. Figure 3 shows four laminations 20', 20'', 20''' and 20'''' where the sheets 20' and 20'' are arranged in the lower layer and the sheets 20''' and 20'''' are arranged in the upper layer. As can be seen in Figure 3, the sheets 20' and 20''' are arranged partially overlapping so that one and the same wedge member (not shown, but intimated at 32') is arranged in the right groove of the sheet 20' and in the left

groove of the sheet 20''. In corresponding manner the sheets 20'' and 20'' are assembled partially overlapping so that one and the same wedge member (not shown, but intimated at 32'') is arranged in the right groove of the sheet 20'' and in the left groove of the sheet 20''. The laminations are thus assembled one by one in order to produce a laminated magnetic core according to the state of the art. As pointed out in connection with Figure 2, each lamination must be bent sufficiently to allow assembly.

Figure 4 shows a side view of a stack member and a part of wedge members in a laminated magnetic core according to a first embodiment of the present invention. Each stack member 40 comprises a number of metal sheets joined together. The metal sheets may have a thickness of 0.35 - 0.50 mm, for instance. Each stack member 40 comprises 50 - 100 sheets, for instance, which have been glued together. Each stack member 40 comprises two identical grooves 42 arranged along the outer long side of the stack member 40. As can be seen in Figure 4, the inner and outer long sides of the stack member 40 have different radii of curvature so that when the stack members 40 are assembled to a laminated magnetic core it will be cylindrical. The stack members 40 are also provided with a number of slots 44 arranged along the inner long side of the stack member 40. These slots 44 are intended for the stator windings in the assembled laminated magnetic core. The laminated magnetic core also comprises wedge members 46 (shown only partially) which are arranged on the stator frame (not shown) and have a dovetail-shaped cross section at the end shown (see also Figure 5). The grooves 42 arranged along the outer long side of the stack member 40 have an inclined flank 48 and a straight, perpendicular flank 50. As can be seen in Figure 4, both the inclined flanks 48 face the same way, i.e. they do not face each other as is the case with the lamination shown in Figure 2. Furthermore, the entrance of the groove 42 is wider than the greatest width of the wedge member 46. This is shown even more clearly in Figure 5. The main reason for the grooves 42 being shaped like this is that the stack members, comprising 50 - 100 laminations glued together, cannot be bent as is the case with individual laminations according to Figure 2. When assembling a laminated magnetic core a stack member 40 is positioned by the two wedge members 46 being inserted into the grooves 42, after which the stack member 40 is displaced to the right in this case so that the inclined flanks 48 abut the dovetail shape of the wedge member. This stack member 40 is thus secured against clockwise movement in tangential direction. The next, partially

overlapping stack member 40' (see Figures 5 and 6) to be assembled is first mirror-inverted so that the inclined flanges 48' of the grooves 42' are on the right instead of the left side of the grooves 42, 42'. Thereafter the mirror-inverted stack member is positioned by inserting the two wedge members 46 into the grooves 42', after which the stack member is displaced to the left in this case so that the inclined flanks 48' abut the dovetail shape of the wedge members 46. This stack member 40' is thus secured against counter-clockwise movement in tangential direction. The arrangement of a locking member at the transition between the stack members 40 and 40' in this position, causes these stack members 40 and 40' to be secured against tangential movement in both directions. This locking member may consist of a spot weld. (See Figure 6.)

Figure 6 shows a side view of a laminated magnetic core in accordance with the invention. As can be seen in Figure 6 the stack members are arranged in different layers and partially overlapping like bricks in a wall, for instance. The stack members in alternative layers are indicated by reference designations 40 and the stack members in the other layers are indicated by reference designations 40'. This means that the stack members 40' are mirror-inverted in relation to the stack members 40. It also means that all stack members 40 are secured against counter-clockwise movement in tangential direction thanks to being locked against the wedge members. This is indicated by the arrow A in Figure 6. The stack members 40', on the other hand, are secured against clockwise movement in tangential direction, thanks to their being locked against the wedge members. This is indicated by the arrow B in Figure 6. If now locking members 52 in the form of spot welds 52 are arranged at at least alternate transitions between stack members 40 secured against counter-clockwise movement in tangential direction and stack members 40' secured against clockwise movement in tangential direction, tangential movement is prevented between the different layers. One variant is to arrange a linear weld instead of these spot welds 52.

The grooves in the stack members intended for the wedge member need not have the cross section illustrated. The grooves may also have dovetail shape and still provide a similar function to that described in connection with Figures 4 - 6. If dovetail-shaped grooves are used the stack members in alternate layers need not be mirror-inverted. On the other hand, different stack members must be made for each layer. This is because, when the laminated magnetic core is assembled the



slots 44 for the stator windings must coincide. The slots 44 cannot therefore be arranged in the same way for stack members intended for different layers.

Figure 7 shows a side view on an enlarged scale of how stack members in different layers are joined together by means of the wedge member in a laminated magnetic core according to a second embodiment of the present invention. As can be seen in Figure 7 the wedge member 70 does not have a dovetail-shaped cross section, but two protrusions 72 arranged symmetrically in relation to the longitudinal axis of the wedge member 70. In this example the cross section of the protrusion 72 is in the shape of a semi-circle. Figure 7 also shows part of a stack member 74 located in one layer and a stack member 74' located in an adjacent layer. Each stack member 74, 74' is provided with two grooves 76, 76' (only one groove is shown in the Figure) in a corresponding manner to the embodiment shown in Figures 4 - 5. The grooves 76, 76' have a part in the form of a recess 78, 78' with a form that fits the protrusion 72 on the wedge member 70. In this example the cross-sectional shape of the recess 78, 78' is a semi-circle. The grooves 76, 76' are then defined by a straight, perpendicular flank 80, 80. As can be seen in Figure 7 the entrance to the grooves 76, 76' is larger than the greatest width of the cross section of the wedge member 70. The recess 78 of the groove 76 in the stack member 74 abuts the left-hand protrusion 72 of the wedge member 70 and secures the stack member 74 against clockwise movement in tangential direction. The recess 78' of the groove 76' in the stack member 74' abuts the right-hand protrusion 72 of the wedge member 70 and secures the stack member 74' against counter-clockwise movement in tangential direction. By applying a spot weld (not shown) in a manner corresponding to that described with reference to Figure 6, the stack members 74, 74' are secured against tangential movement in both directions.

The cross sections of the recess of the wedge member and of the grooves intended for the wedge member need not be limited to the embodiments shown. The protrusion on the wedge member may be rectangular, for instance. The important thing is that the groove has at least one part with complementary shape to said protrusion so that locking occurs in a tangential direction when the groove is in contact with the protrusion on the wedge member.

35

Figure 8 shows an alternative embodiment of the invention used for stack members where the slots 44b for the cable windings have a profile similar to a bicycle chain so that each cable part (in the Figure symbolised by a small circle) is situated in a wider part of the slot, and these parts are separated by narrower waist parts.

The invention is not limited to the embodiments shown. Several modifications are feasible within the scope of the invention.

## CLAIMS

1. A laminated magnetic core for rotating electric machines, characterized in that said laminated magnetic core comprises a number of stack members (40, 40'; 74, 74'), each consisting of a number of sheets of metal joined together, each stack member (40, 40'; 74, 74') being provided with two identical grooves (42, 42'; 76, 76') arranged to cooperate with wedge members (46; 70), the cross-sectional area of the groove (42, 42'; 76, 76') being larger than the cross-sectional area of the wedge member (46; 70), the wedge member (46; 70) having two protrusions (43; 72) arranged symmetrically in relation to the longitudinal axis of the wedge member, said groove (42, 42'; 76, 76') having at least one part shaped to fit said protrusion (72), the stack members (40, 40'; 74, 74') in the laminated magnetic core being stacked on and partially overlapping each other to form different layers of stack members (40, 40'; 74, 74'), the grooves (42, 42'; 76, 76') in the stack members (40, 40'; 74, 74') in the various layers being arranged substantially opposite each other with the wedge members (46; 70) arranged in the grooves (42, 42'; 76, 76') with a protrusion (43; 72) abutting the complementary shape of the groove (42, 42'; 76, 76') in such a manner that the stack members (40; 74) in one layer are secured counter-clockwise in tangential direction and that the stack members (40'; 74') in at least one of the adjacent layers are secured clockwise in tangential direction, and also in that the laminated magnetic core includes locking members (52) arranged at least at the transition between layers secured clockwise and layers secured counter-clockwise in order to prevent tangential movement between the different layers.

2. A laminated magnetic core as claimed in claim 1, characterized in that the at least one part of each groove (42, 42'; 76, 76') with a shape complementary to the protrusion (72) of the wedge member (46; 70), is arranged on the same side of the grooves (42, 42'; 76, 76') in each stack member (40, 40'; 74, 74').

3. A laminated magnetic core as claimed in claim 2, characterized in that the wedge member (46) has dovetail-shaped cross section, and in that the entrance to the groove (42, 42') is larger than the greatest width of the cross section of the wedge member (46).

4. A laminated magnetic core as claimed in claim 3, characterized in that the cross section of the groove (42, 42') has one part with a shape complementary to said dovetail shape and one part which is rectangular in shape.

5

5. A laminated magnetic core as claimed in any of claims 1-4, characterized in that the stack members (40, 40'; 74, 74') in the various layers are arranged in such a manner that the stack members (40; 74) in one layer are mirror-inverted in relation to the stack members (40'; 74') in at least one of the adjacent layers.

10

6. A laminated magnetic core as claimed in claim 5, characterized in that each groove has dovetail-shaped cross section.

15

7. A laminated magnetic core as claimed in any of claims 1-6, characterized in that said locking device (52) consists of a spot weld (52), said spot welds (52) being arranged so that each stack member (40, 40'; 74, 74') is joined by spot welds to two other stack members (40, 40'; 74, 74') arranged in an adjacent layer.

20

8. A laminated magnetic core as claimed in any of claims 1-6, characterized in that said locking means consists of a linear weld that joins all adjacent layers of stack members (40, 40'; 74, 74') with each other.

25

9. A laminated magnetic core as claimed in any of claims 1-8, characterized in that each stack member (40, 40'; 74, 74') comprises an equally large number of metal sheets, and that said number is 50 - 100.

30

10. A rotating electric machine comprising a laminated magnetic core as claimed in any of claims 1-9.

## AMENDED CLAIMS

[received by the International Bureau on 31 March 1998 (31.03.98) ;  
original claims 1 and 3 amended ; remaining claims unchanged (2 pages)]

1. A laminated magnetic core for rotating electric machines, wherein said laminated magnetic core comprises a number of stack members (40, 40'; 74, 74'), each consisting of a number of sheets of metal joined together, each stack member (40, 40'; 74, 74') being provided with two identical grooves (42, 42'; 76, 76') arranged to cooperate with wedge members (46; 70), designed to join said stack members (40, 40'; 74, 74') together, **characterized** in that the cross-sectional area of the groove (42, 42'; 76, 76') being larger than the cross-sectional area of the wedge member (46; 70), and in that the entrance to the groove (42, 42') is larger than the greatest width of the cross section of the wedgemember (46; 70), the wedge member (46; 70) having two protrusions (43; 72) arranged symmetrically in relation to the longitudinal axis of the wedge member, said groove (42, 42'; 76, 76') having at least one part shaped to fit said protrusion (72),  
15 the stack members (40, 40'; 74, 74') in the laminated magnetic core being stacked on and partially overlapping each other to form different layers of stack members (40, 40'; 74, 74'), the grooves (42, 42'; 76, 76') in the stack members (40, 40'; 74, 74') in the various layers being arranged substantially opposite each other with the wedge members (46; 70) arranged in the grooves (42, 42'; 76, 76') with a protrusion (43; 72) abutting the complementary shape of the groove (42, 42'; 76, 76') in such a manner that the stack members (40; 74) in one layer are secured counter-clockwise in tangential direction and that the stack members (40'; 74') in at least one of the adjacent layers are secured clockwise in tangential direction, and also in that the laminated magnetic core includes locking members (52) arranged  
20 at least at the transition between layers secured clockwise and layers secured counter-clockwise in order to prevent tangential movement between the different layers.
2. A laminated magnetic core as claimed in claim 1, **characterized** in that the at least one part of each groove (42, 42'; 76, 76') with a shape complementary to the protrusion (72) of the wedge member (46; 70), is arranged on the same side of the grooves (42, 42'; 76, 76') in each stack member (40, 40'; 74, 74').
3. A laminated magnetic core as claimed in claim 2, **characterized** in that the wedge member (46) has dovetail-shaped cross section.

4. A laminated magnetic core as claimed in claim 3, **characterized** in that the cross section of the groove (42, 42') has one part with a shape complementary to said dovetail shape and one part which is rectangular in shape.

5. A laminated magnetic core as claimed in any of claims 1-4, **characterized** in that the stack members (40, 40'; 74, 74') in the various layers are arranged in such a manner that the stack members (40; 74) in one layer are mirror-inverted in relation to the stack members (40'; 74') in at least one of the adjacent layers.

6. A laminated magnetic core as claimed in claim 5, **characterized** in that each groove has dovetail-shaped cross section.

7. A laminated magnetic core as claimed in any of claims 1-6, **characterized** in that said locking device (52) consists of a spot weld (52), said spot welds (52) being arranged so that each stack member (40, 40'; 74, 74') is joined by spot welds to two other stack members (40, 40'; 74, 74') arranged in an adjacent layer.

8. A laminated magnetic core as claimed in any of claims 1-6, **characterized** in that said locking means consists of a linear weld that joins all adjacent layers of stack members (40, 40'; 74, 74') with each other.

9. A laminated magnetic core as claimed in any of claims 1-8, **characterized** in that each stack member (40, 40'; 74, 74') comprises an equally large number of metal sheets, and that said number is 50 - 100.

10. A rotating electric machine comprising a laminated magnetic core as claimed in any of claims 1-9.

1 / 3

Fig. 1




Fig. 2





Fig. 3







2 / 3

Fig. 4




Fig. 5





Fig. 6



3 / 3

Fig. 7





Fig. 8





## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01842

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H02K 1/18

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 292999 A (SIEMENS-SCHUCKERTWERKE AKTIENGESELLSCHAFT), 11 April 1929 (11.04.29), see the whole document --	1,2,5,10
A	US 1756672 A (J.M. BARR), 29 April 1930 (29.04.30), see the whole document --	1-10
A	DE 508181 C (SIEMENS-SCHUCKERTWERKE AKT.-GES.), 25 Sept 1930 (25.09.30), see the whole document -----	1-10

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

4 March 1998

Date of mailing of the international search report

05 -03- 1998

Name and mailing address of the ISA:

Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Håkan Sandh  
Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

03/02/98

International application No.

PCT/SE 97/01842

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
GB	292999	A	11/04/29	NONE	
US	1756672	A	29/04/30	NONE	
DE	508181	C	25/09/30	NONE	